

# Drupal7?????

- [\[1\] Nginx FastCGI \[2\] AMP\[3\] conf](#)
- [Drupal7 Optimizing \[4\]](#)
- [Views PHP](#)
- [Windows 11\[5\]\[6\]\[7\]](#)

# ?? Nginx FastCGI ??AMP???

## conf

##### drupal##### amp#####  
##### \*?amp##### drupal[] cookie[] ?

```
fastcgi_cache_path /etc/nginx/cache levels=1:2 keys_zone=tainanoutlook:200m max_size=10g
inactive=2h use_temp_path=off;
fastcgi_cache_key "$scheme$request_method$host$request_uri";
fastcgi_ignore_headers Cache-Control Expires Set-Cookie;

set $skip_cache 1;

if ($request_uri ~* "/*.*?amp") {
    set $skip_cache 0;
}

include snippets/fastcgi-php.conf;
fastcgi_cache tainanoutlook;
fastcgi_cache_valid 200 301 302 2h;
fastcgi_cache_use_stale error timeout updating invalid_header http_500 http_503;
fastcgi_cache_min_uses 1;
fastcgi_cache_lock on;
fastcgi_cache_bypass $skip_cache;
fastcgi_no_cache $skip_cache;
add_header X-FastCGI-Cache $upstream_cache_status;
```

# Drupal7 Optimizing ????

☐ chained\_fast ☐ apcu ☐ registry\_autoload ☐ xautoload

```
drush en chained_fast apcu registry_autoload xautoload expire -y
```

```
vi sites/default/settings.php
```

```
$conf['cache_backends'][] = 'sites/all/modules/apcu/apcu.cache.inc';
$conf['cache_backends'][] = 'sites/all/modules/chained_fast/chained_fast.cache.inc';

// Chained fast configuration.
$conf['chained_fast']['fast_backend'] = 'DrupalAPCuCache';

// Cache class configuration - This uses chained_fast for all caches except the form cache.
This might not be suitable for all sites, but is a good default.
$conf['cache_default_class'] = 'ChainedFastBackend';
$conf['cache_class_cache_form'] = 'DrupalDatabaseCache';
```

admin/config/development/performance ☐ ☐ ☐ ☐

--	--	--	--	--	--	--	--	--

--	--	--	--

--	--	--	--	--	--

TTTTT CSS TT

JavaScript

### Self-updating APCu classmap (\*) (Running and available)

APC (Running and available)

APCu (Running and available)

XCache (Not currently available)

### Self-updating database classmap (\*) (Running and available)

Postpone registration of module namespaces until the first cache miss (recommended)

Replace core class loader.

expire (Cache Expiration)

Status of implementation ☐ Internal expiration

Modules that support external expiration ☐ Include base URL in expires

Node expiration Node actions 

PS. \_\_\_\_\_

--	--	--	--	--

## Drupal

# Views PHP

Drupal 7 [views\\_php](https://www.drupal.org/project/views_php) [https://www.drupal.org/project/views\\_php](https://www.drupal.org/project/views_php)

`field_dow`

```
<?php
// 取得 $data 物件
$field_dow = $data->_field_data['nid']['entity']->field_dow['und'];

// 取得 [field_dow] 值
$dow_values = array_map(function($item) {
    return $item['value'];
}, $field_dow);

// 輸出
echo implode(' ', $dow_values);
?>
```

`field_dow` 1 7 `field_dow` `field_dow`

```
<?php
// 取得 $data 物件
$field_dow = $data->_field_data['nid']['entity']->field_dow['und'];

// 取得 [field_dow] 值
$weekdays = [
    1 => '日',
    2 => '一',
    3 => '二',
    4 => '三',
    5 => '四',
    6 => '五',
    7 => '六'
];

// 取得 [field_dow] 值
$dow_names = array_map(function($item) use ($weekdays) {
```

```
        return $weekdays[$item['value']];
    }, $field_dow);

// 输出
echo implode(' ', $dow_names);

?>
```

?>

[illegible]

 Views Day of Week (views\_dow)

# Windows 11?????????

powercfg.exe /hibernate off

